

PRE-LEASE BUILDING SECURITY PLAN

OFFEROR'S PRE-LEASE BUILDING SECURITY PLAN  
EVALUATION FOR AN OFFICE BUILDING

The Offeror must complete a report based on a walk through of the building, parking areas, and structure's perimeter that includes the review of windows or window systems, facade protection level, and perimeter evaluation.

The Offeror states, as part of this offer, that the proposed space/building is as described below and contains the identified features and devices. Should this exhibit not provide sufficient space to respond adequately to any question, additional pages should be attached.



**BUILDING ADDRESS**  
 BUILDING NAME: 7701 STEMMONS  
 BUILDING ADDRESS: 7701 STEMMONS FREEWAY  
 CITY: DALLAS  
 STATE: TX  
 Year Built: 1965      Year Last Renovated: 2052

**SIZE AND LAYOUT**  
 The following information applies to (check one):  
 an existing building  
 a building planned for lease construction

Space offered to Government (By Floor):  
 Approximate gross area of typical floor (identify atypical floors in dividually)  
 Building Height in Feet: 110 feet  
 Number of Stories Above Grade: 8  
 Number of Stories Below Grade: 1

**OTHER OCCUPANCIES IN BUILDING (Check All That Apply)**  
 Restaurants:   
 Laboratories: \_\_\_\_\_  
 Storage: \_\_\_\_\_  
 Retail: \_\_\_\_\_  
 Day Care Center: \_\_\_\_\_

Other, list: \_\_\_\_\_

Pre-lease Exhibit, Security Evaluation p. 7  
 Lessor  Gov't 

PRE-LEASE BUILDING SECURITY PLAN

GENERAL INFORMATION

Provide digital pictures of the building. Include exterior views showing the front of the building and all sides of the building.

Identify the number of stories of the building (above and below grade)



Identify the approximate gross square footage per floor in the building.

Identify the proposed floors offered to the Government to occupy

<u>Exterior Materials</u>	<u>Yes</u>	<u>No</u>
Brick		✓
Block		✓
Concrete – Precast		✓
Concrete – Poured	✓	
Metal Panels		✓
Glass Exterior	✓	

Answer each question below, then, identify and discuss measures to be taken to protect and secure utilities.

<u>Question</u>	<u>Yes</u>	<u>No</u>
Is the water supply to the building protected?	✓	
Is the main unit of air/ventilation system accessible to the public?		X
Is the wire closet locked?	✓	
Is utility access locked?	✓	
Is there exterior access to the electric service?		✓
Is there exterior access to the gas service?		✓
Is there exterior access to the water service?		✓
Is there exterior access to the telephone service?		✓
Is there exterior access to any other heating source?		✓
Is fuel stored within the building?		✓
Are there exterior propane fuel tanks?		✓
For the facilities with exterior propane fuel tanks, are they protected?	N	A

Pre-lease Exhibit, Security Evaluation p. 3  
 Lessor  Gov't 

PRE-LEASE BUILDING SECURITY PLAN

PERIMETER INFORMATION

<u>General Public Access</u>	<u>Distance in Feet</u>
Distance in feet from the building to the nearest public street.	129
Distance in feet from the building to the nearest public on-street parking.	NONE
Distance in feet from the building to the nearest public parking lot.	NONE

Provide a site sketch showing perimeter distances.

Describe the building's emergency lighting system.

Identify and describe the lighting levels provided at entrances/exits, garages, parking lots or other adjacent areas to the building to discourage "crimes against persons".

Identify and describe if emergency power is provided within the building.

If emergency power for life safety systems is provided by generator(s) or UPS systems describe if they are tested and maintained in accordance with NFPA 110 or NFPA 111, as applicable.

Identify and describe any garage or parking area control or surveillance systems in place.

Identify and describe the location of mechanical areas, along with protocol and procedures taken to secure these areas to ensure access by only authorized personnel.

Identify and describe roof access and the roof security, along with protocol and procedures taken to secure the roof to ensure access by only authorized personnel.


Identify and describe alarm/emergency notification system.

Review and evaluate the occupancy emergency plan.

Identify and describe [redacted] system, including,

- Typical size
- Thickness of panes
- Type of frame
- Type of anchorage
- Number of windows
- Type of glass
- Type of configuration (single-pane, insulated, laminated, etc.)
- [redacted] (if installed)
- Date film was installed

If the proposed [redacted] is less than the [redacted] thickness specified in the SFO, a licensed professional engineer shall complete the evaluation specified below.

Lessor  Gov't 

PRE-LEASE BUILDING SECURITY PLAN


For Build-to-Suit Solicitations and Alternative Blast Mitigation Proposals

A registered Professional Engineer shall complete the evaluations for window glazing and facade protection. The Professional Engineer's stamp (professional license) must be placed on the report.

For Build-to-Suit solicitations, identify and describe window systems in accordance with WINGARD 4.1 or later or WINLAC 4.3 software using the test methods provided in the US General Services Administration *Standard Test Method for Glazing and Window Systems Subject to Dynamic Overpressure Loadings* or F1642-04 *Standard Test Method for Glazing and Window Systems Subject to Dynamic Loadings* - ASTM International.

For Build-to-Suit solicitations, identify and describe the facade protection level as prescribed by WINGARD 4.1 or later or WINLAC 4.3 software.

For Build-to-Suit solicitations, identify and describe the distance from the face of the building's exterior to the protected/defended perimeter (i.e., any potential point of explosion), around the complete circumference of the structure's exterior. This would mean the distance from the building to the curb or other boundary protected by bollards, planters or other barrier. All potential points of explosion must be evaluated that could be accessible by any motorized vehicle (i.e. street, alley, sidewalk, driveway, parking lot).



PRE-LEASE BUILDING SECURITY PLAN

STATEMENT OF PROFESSIONAL ENGINEER

I hereby attest that I have performed an assessment of the subject premises; and that the above information is complete and accurate to the best of my knowledge. I have initialed at the bottom of each page. My official stamp, professional license information, and signature are affixed below.

I HAVE INCLUDED FINDINGS, RECOMMENDED CORRECTIVE ACTION(S), AND MADE SPECIFIC REFERENCES TO THE APPLICABLE CODE SECTIONS OR SECURITY REFERENCE DOCUMENTS AS AN ATTACHMENT TO THIS REPORT. SUCH FINDINGS SPECIFICALLY IDENTIFY INSTANCES WHERE THE BUILDING DOES NOT COMPLY WITH THE SPECIFIED CRITERIA, AND RECOMMENDATIONS HAVE BEEN MADE IN ORDER TO RECTIFY THE SITUATION AND ASSURE SUBSTANTIAL COMPLIANCE OF THE BUILDING TO ALL APPLICABLE CRITERIA.

*(if no deficiencies were identified, during the evaluation, please explicitly state so in the findings and recommendations portion of the report)*

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Printed Name: \_\_\_\_\_

Name of Firm: \_\_\_\_\_

Phone #: (\_\_\_\_) \_\_\_\_\_

License Number: \_\_\_\_\_

Stamp Here:

PRE-LEASE BUILDING SECURITY PLAN

OFFEROR'S STATEMENT OF CORRECTION

In the event any of the offered space does not meet the minimum specified performance conditions '3b' using the test methods provided in the U.S. General Services Administration Standard Test Method for Glazing and Window Systems Subject to Dynamic Overpressure Loadings or F1642-04 Standard Test Method for Glazing and Clazing Systems Subject to Airblast Loadings - ASTM International, the Offeror shall attach a sheet describing the exact nature of the deficiency and will bring the offered space up to compliance with all applicable criteria to complete at the Offeror's sole cost and expense prior to the Government's acceptance of the offered space under the terms of any prospective lease agreement.

The Offeror shall attest below that the government, may implement all security operating standards. The base building security standards may include additional performance criteria for facade and setback, if feasible.

NOTE: REPORTS SUBMITTED WITHOUT RECOMMENDED CORRECTIVE ACTIONS WILL BE RETURNED WITHOUT REVIEW

Signature: \_\_\_\_\_ Date: 10-22-2010

Printed Name: John W. Moss

Title: VP - E

Name of Firm: Stroman Stammers GP, Inc